

- **11kw AC EV Charger**
- **2.8"LCD display**
- **RFID,WIFI-APP,OCCP**
- **Type2 connector**



<b>Product Model</b>	<b>EVB-316-TC2</b>
Dimension(mm)	360mm(L)* 193mm (W) *170mm(H)
Color	White,Black, Blue, Gray,Orange
HMI	2.8" LCD display( optional )
AC Power	AC 380~480V ( three phase )
Communication protocol	OCCP 1.6J
Rated Current	16A
Charging Power	11kW
Rated Frequency	50/60Hz
Connector type	Type 2 connector
Elevation	≤2000m
Working temperature	-20℃~+50℃
Working Humidity	Up to 95% non-condensing
Storage temperature	-30℃~+75℃
Charging Mode	Plug and Charge (RFID,WIFI and OCCP are optional)
Protection Function	Overvoltage, undervoltage, overcurrent, short circuit, leakage, etc.
Leakage Protection	TypeB (AC30mB + DC6mA)
Cable Length	5m (customizable )
Protection Level	IP55
Installation	Wall-mounted or floor-mounted installation
Certificate	TUV Certification
weight (kg)	5.3kg
warranty	2 years



Scan the QR code below  
find more about AC EV Charger,  
EV Charging Cable

